

Material Safety Data Sheet

Distributor: Innovative Vacuum Solutions, Inc.
31B Pulpit Rock Road
Pelham, NH 03076

Emergency Telephone: (603) 635-1480
(800) 441-6825

Prepared By: Michael Metropolis

Date: June 2002

Section One: General Information


Product Code: **405200**

Product Name: **IVS 19**

NFPA DIAMOND

FLAMMABILITY

HEALTH HAZARD



REACTIVITY

SPECIAL

CAS NUMBER: 64742-65-0

CHEMICAL FORMULA: $(CH_2)_n$ $20 \leq n \leq 40$

GENERIC NAME: Solvent Refined Neutral Paraffinic Oil

SECTION TWO: REGULATED INGREDIENTS (29 CFR 1910 . 1200)

REGULATED MATERIALS AT CONCENTRATIONS OF 1% (WT) OR GREATER NO HAZARDOUS INGREDIENTS. MATERIAL IS 100% NEUTRAL PARAFFINIC OIL. MATERIAL HAS BEEN SUBJECT TO SEVERE SOLVENT REFINING.

SECTION THREE: HEALTH HAZARDS

POSSIBLE ENTRY ROUTES: Ingestion, Inhalation of oil mists

TARGET ORGANS: None known

EFFECTS OF EXPOSURE

ACUTE EFFECTS: Exposure to oils mists may cause nausea and eye irritation. Detailed studies have not been made, but material is not expected to be dermatitic or sensitizer.

CHRONIC EFFECTS: Unknown

FIRST AID PROCEDURES: Skin – wash with soap and water. Eyes – flush with water. Contact a physician!
Ingestion – give liquids and induce vomiting if victim is conscious. Contact a physician! Small amounts in mouth may be washed out.

REFERENCES: None

SECTION FOUR: FIRE AND EXPLOSION DATA

FLASH POINT: > 213 C

METHOD USED: Cleveland Open Cup

EXPLOSIVE LIMITS: Lower - Unknown
Upper - Unknown

EXTINGUISHING MEDIA: Water Fog, Chemical Foam or Carbon Dioxide

SPECIAL FIREFIGHTING PROCEDURES: Wear breathing gear when fighting fires in enclosed spaces; incomplete combustion of this material produces carbon monoxide!

USUAL FIRE AND/OR EXPLOSION HAZARDS: None

SECTION FIVE: PHYSICAL PROPERTIES

PHYSICAL STATE: Liquid

VAPOR PRESSURE: < .001 Torr @ 25

BOILING POINT: > 200 C

EVAPORATION RATE (other = 1): Nil

VAPOR DENSITY: approximately 14

WT % VOLATILES: Nil

SPECIFIC GRAVITY: .87 gm/ml

VISCOSITY: 54 cst @ 40 C

SOLUBILITY IN WATER: Nil

APPEARANCE: Pale yellow, viscous liquid with faint petroleum odor.

SECTION SIX: REACTIVITY

STABILITY: Material is stable

CONDITIONS TO AVOID: Continuous exposure to temperatures > 200 C

INCOMPATIBILITY (MATERIAL TO AVOID): Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide

SECTION SEVEN: RELEASE PROCEDURES

PROCEDURES TO BE FOLLOWED IN EVENT OF RELEASE: Small spills may be wiped up with a rag. Large spills should be picked up immediately with an absorbent.

PROCEDURES FOR PROPER WASTE DISPOSAL: Proper waste disposal procedures are dependent on the product's enduses. Check applicable Federal, State and Local regulations covering treatment, storage and disposal of your process effluents.

SECTION EIGHT: SPECIAL PROTECTION

RESPIRATORY PROTECTION: See ventilation notes for

VENTILATION: US Govt. 8 hr TWA limit

PROTECTIVE GLOVES: Yes-made of oil impermeable rubber

exposure to all oil mists in 5 mg pr cubic feet

SAFETY GLASSES/GOGGLES: Yes – with side shield limit

LOCAL EXHAUST: required to meet above

OTHER PROTECTIVE EQUIPMENT: None should be required Under normal use

MECHANICAL EXHAUST: same as above
OTHER REQUIREMENTS: none

SECTION NINE: SPECIAL PROTECTION

SPECIAL HANDLING PRECAUTIONS: None

SPECIAL STORAGE PRECAUTIONS: None

ADDITIONAL INFORMATION: NFPA Class III B material